

AGRI TRAC EXTRA 10W40

UNIVERSAL MOTOR OIL FOR TRACTORS.

AGRI TRAC EXTRA 10W40 is an universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems for tractors.

AGRI TRAC EXTRA 10W40 meets the following specifications:

- API CF-4, CE/SF
GL 4, GL 5 (low speed/ high torque)
- CASE NEW HOLLAND MAT 3525, 3526
- FORD ESN-M2C-159 B/C
ESN-M2C-121 C
ESN-M2C-86 A/B
ESN-M2C-134 C/D
- ACEA E2/E3
- MAN 271
- MB 227.1
- MASSEY FERGUSON M-1127
M-1135
M-1139
M-1144
- ALLISON C-4
- ZF TE-ML 06B, 07B
- CATERPILLAR TO-2

ADVANTAGES :

- Special composition on "hydrocracked" base oil.
- Large temperature field and lower fuel consumption.
- Good detergent and dispersant properties.
- Good resistance against ageing.
- Long lifetime.
- Only one oil for the lubrication of all tractor parts.
- Meets the requirements of most manufacturers.

SPECIFICATIONS :

This multigrade oil is advised for the lubrication of either charged or not charged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-highway equipment.

TYPICAL CHARACTERISTICS :

<i>Test</i>	<i>Method</i>	<i>Average result</i>
SAE-class		10W40
Density at 15°C	D 4052	875 kg / m ³
Viscosity at 40°C	D 445	96 cSt
Viscosity at 100°C	D 445	14.1 cSt
Viscosity index	D 2270	150
Viscosity at -25°C	D 2983	7.000 cP
Flash point COC	D 92	220 °C
TBN	D 2896	10.7 g KOH/kg
Pour point	D 6892	-35 °C

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.