

AGRI TRAC

UNIVERSAL MOTOR OIL FOR TRACTORS.

AGRI TRAC is an universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems for tractors. Herefore can one single oil be used for the lubrication of different tractor parts.

This multigrade oil is advised for the lubrication of either charged or not charged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-highway equipment.

Viscosity classes : 10W30, 15W30, 15W40 and 20W40.

AGRI TRAC meets the following specifications:

- API CF-4, CE/SF
GL 4, GL 5 (low speed/ high torque)
- CASE NEW HOLLAND MAT 3525, 3526
- FORD ESN-M2C-159 B/C
ESN-M2C-134 C/D
- ACEA E2/E3
- MAN 271
- MB 227.1
- ZF TE-ML 06A & B, 07B
- JOHN DEERE JDM J27
- MASSEY FERGUSON M-1127
M-1135
M-1139
M-1144
- NEW HOLLAND NH 330G (15W40)
NH 030C (10W30)
NH 024C (15W40)
- MIL MIL-L-2104 D/C
MIL-L-2105
MIL-L-46152 B

ADVANTAGES :

- Good protection against corrosion.
- Good detergent and dispersant properties.
- Good resistance against ageing.
- Long lifetime.
- Only one oil for the lubrication of all tractor parts.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result			
			10W30	15W30	15W40	20W40
SAE-class			10W30	15W30	15W40	20W40
Density at 15°C	D 4052	kg / m ³	881	887	886	890
Viscosity at -25°C	D 5293	cP	6700	-	-	-
Viscosity at -20°C	D 5293	cP	-	6600	6600	-
Viscosity at -15°C	D 5293	cP	-	-	-	6900
Viscosity at 40°C	D 445	cSt	75	81,7	110	115
Viscosity at 100°C	D 445	cSt	11,4	10,8	13,7	14,5
Viscosity index	D 2270		144	118	123	128
Pour point	D 6892	°C	-35	-35	-34	-27
TBN	D 2896	g KOH/kg	10,7	10,7	10,7	10,7
Flash point COC	D 92	°C	216	222	222	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.