

POWER 2T ZTT

SEMI-SYNTHETIC OIL FOR AIR COOLED 2-STROKE GASOLINE ENGINES.

POWER 2T ZTT is a semi-synthetic prediluted oil, intended for the lubrication of 2-stroke gasoline engines with a high specific power.

POWER 2T ZTT meets the following specifications:

- API TC
- JASO FB
- ISO-L EGB

ADVANTAGES :

- High lubricant power.
- Very high thermal stability.
- No deposit formation.
- Easily miscible with gasoline.
- Efficient protection against rust.

APPLICATIONS :

This oil is especially manufactured in order to satisfy the requirements of up-to-date air cooled 2-stroke engines with a high specific power.

For instance: Suzuki, Kawasaki, Yamaha, etc.

TYPICAL CHARACTERISTICS :

Test	Method	Average result
Density at 15°C	D 4052	882 kg / m ³
Viscosity at 40°C	D445	78,4 cSt
Viscosity at 100°C	D 445	10,2 cSt
Viscosity index	D 2270	112
Pour point	D 6892	-15 °C
TBN	D 2896	1,1 g KOH/kg
Flash point	D 92	100 °C
Sulphated ash content	D 874	0,28 mass %

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

