

POWER 2T

OIL FOR AIR COOLED 2-STROKE GASOLINE ENGINES.

POWER 2T is an oil for air cooled 2-stroke gasoline engines, intended for machines, of which the fuel tank is filled with a mixture of gasoline and oil, and also for machines, equipped with separate tanks.

POWER 2T meets the following specifications:

- API TC

ADVANTAGES :

- Easily miscible with gasoline.
- Very high lubricant power.
- High thermal stability.
- Very good protection of the pistons and segments against overheating.
- No deposit formation.
- Efficient protection against rust at every temperature.

APPLICATIONS :

This oil is applicable for all air cooled 2-stroke gasoline engines with a dilution content of 2% (1 to 50) and 4% (1 to 25). This according to the constructors' requirements.

TYPICAL CHARACTERISTICS :

Test	Method	Average result
Colour		red
Density at 15°C	D 4052	877 kg / m ³
Viscosity at 40°C	D 445	55,3 cSt
Viscosity at 100°C	D 445	8,3 cSt
Viscosity index	D 2270	121
Pour point	D 6892	-30 °C
TBN	D 2896	1,1 g KOH/kg
Flash point COC	D 92	106 °C

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

