

# RACING PLUS 10W60

## FULLY SYNTHETIC RACING MOTOR OIL.

RACING PLUS 10W60 is a fully synthetic engine oil of the latest generation, for the lubrication of all high performance engines.

RACING PLUS 10W60 meets the following specifications:

- API SL/CF
- BMW M-engines
- ACEA A3/B3

### ADVANTAGES:

- Excellent fluidity at low temperature.
- Very low resistance at start.
- Exceptional viscosity index.
- Very high thermal stability.

### APPLICATIONS:

- 4-stroke gasoline engines, multi-valves, turbo.
- 4-stroke passenger car diesel engines, with or without turbo.

### TYPICAL CHARACTERISTICS:

Test	Method	Average result
Density at 15°C	D 4052	871 kg / m <sup>3</sup>
Viscosity at 40°C	D 445	171 cSt
Viscosity at 100°C	D 445	24.5 cSt
Viscosity at -30°C	D 5293	6700
Viscosity index	D 2270	175
Pour point	D 6892	-36 °C
TBN	D 2896	9,5 g KOH/kg
Flash point	D 92	238 °C
Sulphated ash	D 874	1,0 mass %

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

