

SYN-TEC F 5W30

SYN-TEC F 5W30 is a synthetic motor oil, which corresponds to the specific requirements of the constructor Ford. The use of special selected additives provides an excellent cleanliness of the motor and protects the exhaust catalyst. Because of the high fluidity, an important fuel economy can be achieved.

SYN-TEC F 5W30 meets the following specifications:

- API SJ
- ILSAC GF-2
- ACEA A1-98/B1-98
- FORD WSS-M2C 913-A and B
- WSS-M2C 912-A

APPLICATIONS :

SYN-TEC F 5W30 is especially developed for the lubrication of modern gasoline and diesel engines with turbo, giving fuel economy benefits.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	855
Viscosity at 40°C	D 445	cSt	56
Viscosity at 100°C	D 445	cSt	10,0
Viscosity at -30°C	D 5293	cP	4750
Viscosity index	D 2270		167
Pour point	D 6892	°C	-39
TBN	D 2896	g KOH/kg	10,4
Flash point COC	D 92	°C	230
Viscosity HT/HS		cP	3,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

