

SYN-TEC PRO 5W30

Full Synthetic « Longlife III » motor oil

SYN-TEC PRO 5W30 is a 100% synthetic, fuel economy "low SAPS" motor oil of the latest generation, which is especially developed to meet the "long life III" requirements of the cars of the constructors Volkswagen, Audi, Skoda and Seat.

The oil meets the VW-norms 504.00 and 507.00. These norms exceed almost all the previous specifications: 502.00 / 503.00 / 503.01 / 505.00 / 506.00 and 506.01. It also meet the following specifications:

- ACEA A3/B4/C2/C3-10
- MB 229.51
- BMW LL-04

APPLICATIONS :

- This oil can be used in all vehicles with extended oil drain intervals, except in V10 TDI and the 5 cylinder 2,5 TDI engines.
- The first generation engines with pump injector units have to use the 505.01 specification.

ADVANTAGES :

- Lower service costs by lower fuel consumption
- A longer working life for exhaust gas treatment systems ("low saps")
- Fuel economy because of low viscosity of the oil.
- Very strong protection against wear. Good lubrication at cold start.
- Very good detergency and dispersion.

TYPICAL CHARACTERISTICS :

Test	Method	Average result
Density at 15°C	D 4052	849 kg / m ³
Viscosity at 40°C	D 445	70 cSt
Viscosity at 100°C	D 445	11.5 cSt
Viscosity at -30°C	D 5293	5600 cP
Viscosity index	D 2270	159
Flash Point COC	D 92	230°C
Pour Point	D 6892	-39°C
TBN	D 2896	5.8 g KOH/kg
Sulphated ash	D 874	0.6%

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

