

SYN-TEC SPECIAL LGO 5W30

SYN-TEC SPECIAL LGO 5W30 is a fully synthetic engine oil of the latest generation, for the lubrication of all gasoline and diesel engines with turbo, giving fuel economy benefits.

This oil meets the following specifications:

- API SL/CF
- ACEA A1-02/A5-02, B1-02/B5-02

ADVANTAGES :

- Excellent fluidity at low temperature.
- Very low resistance at start.
- Exceptional viscosity index.
- Very high thermal stability.
- Fuel Economy formulation.

APPLICATIONS :

- 4-stroke gasoline engines, multi-valves, turbo.
- 4-stroke diesel engines, with or without turbo.

TYPICAL CHARACTERISTICS :

Test	Method	Average result
Density at 15°C	D 4052	858 kg / m ³
Viscosity at 40°C	D 445	66 cSt
Viscosity at 100°C	D 445	11,1 cSt
Viscosity at -30°C	D 5293	6280 cP
Viscosity index	D 2270	162
Pour point	D 6892	-42 °C
TBN	D 2896	10 g KOH/kg
Flash point COC	D 92	214 °C
Sulphated ash	D 874	1,0 mass %

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

