

## ★ SUPER TRACTOR OIL UNIVERSAL

This is a semi synthetic lubricant based on carefully selected highly refined base oils for use in public works. It meets the specifications of most manufacturers, both in terms of engine and gear oils. Its high viscosity index allows the use in all weather conditions.

## ★ APPLICATIONS

Diesel engines with or without turbo and 4-stroke gasoline engines. Without limitation recommended for all uses in the area of off-road equipment : motors, mechanical transmissions, transaxles, hydraulic systems, wet brakes and compressors, pumps and reductions.

## ★ PERFORMANCE LEVEL

- ACEA: E3
- ALLISON : C4 (Agriculture applic.)
- API: CG-4
- API: GL 4
- API: GL 5 (Low speed/high torque)
- API: SF/CE
- CASE: MAT 3525
- CASE: MAT 3526
- CATERPILLAR: TO-2
- EATON VICKERS: I-280-S
- EATON VICKERS: M-2950-S
- FORD: ESN-M2C134 C/D
- FORD: ESN-M2C159 B/C
- FORD: FNH 82009203
- JD: J20C
- JD: J27
- MF: M 1144
- MF: M 1145
- NH: NH 024C
- NH: NH 410B
- NH: NH 420A
- ZF: TE-ML 03A
- ZF: TE-ML 05K
- ZF: TE-ML 06A
- ZF: TE-ML 06B
- ZF: TE-ML 06C
- ZF: TE-ML 07B
- ZF: TE-ML 07D

## ★ FEATURES

Total engine protection : outstanding engine cleanliness and durability

## ★ CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l	ASTM D4052	0.873
Viscosity 40 °C	mm <sup>2</sup> /s	ASTM D445	94
Viscosity 100 °C	mm <sup>2</sup> /s	ASTM D445	14.1
Viscosity Index		ASTM D2270	154
Flash Point COC	°C	ASTM D92	225
Pour Point	°C		-39
Viscosity -25 °C	mPas	ASTM D5293	6550

## ★ PACKAGING

