

★ SUPER TRACTOR OIL UNIVERSAL

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors

★ APPLICATIONS

This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines off-highway equipment.

★ PERFORMANCE LEVEL

- ACEA: E3
- ALLISON : C4 (Agriculture applic.)
- API: CG-4
- API: GL-4
- API: GL-5 (Low speed/high torque)
- API: SF/CE
- CASE: MAT 3525
- CASE: MAT 3526
- EATON VICKERS: M-2950-S
- FORD: ESN-M2C134 C/D
- FORD: ESN-M2C159 B/C
- FORD: FNH 82009203
- JD: J20C
- JD: J27
- MF: M 1135
- MF: M 1139
- MF: M 1143
- MF: M 1144
- MF: M 1145
- NH: NH 024C
- Sauer Sunstrand/Danfoss: Hydro Static Trans Fluid
- ZF: TE-ML 03A
- ZF: TE-ML 05K
- ZF: TE-ML 06A
- ZF: TE-ML 06B
- ZF: TE-ML 06C
- ZF: TE-ML 07B
- ZF: TE-ML 07D



★ FEATURES

Anti-wear and oxidation stability : proven protection of critical parts.

★ CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l	ASTM D4052	0.881
Viscosity 40 °C	mm ² /s	ASTM D445	93.50
Viscosity 100 °C	mm ² /s	ASTM D445	13.00
Viscosity Index		ASTM D2270	137
Flash Point COC	°C	ASTM D9254	218
Pour Point	°C		-35
Total Base Number	mgKOH/g		11.3
Sulphate Ash	%		1.55
Viscosity -20 °C	mPas		6400

★ PACKAGING

